

REQUEST FOR PROPOSAL

Onboarding Service Provider for LAN & Wi-Fi
Networking and Augmenting with the existing
network in the Premises of
Government Polytechnic
Sheohar

RFP: - SHR/10/2024-25 Issued on: 30.08.2024

10

Government Polytechnic Sheohar
Sheohar Bihar
Department of Science, Technology and Technical Education

Page 1 of 44

Government of Bihar

Contents	
1.	Abbreviations and Definitions4
2.	Notice Inviting Tenders 5
3.	Instruction to Bidders 7
4.	Inspection of Site and Equipment8
5.	Tendering Expense8
6.	Right to Accept Any Offer and to Reject Any or All Offers
7.	Language of the tender
8.	Taxes
9.	Concessions permissible under statutes 8
10.	Amendments to Tender Documents
11.	Pre-Bid Meeting9
12.	Earnest Money Deposit (EMD)
13.	Bid Validity9
14.	Licensing9
15.	Signing of the Contract
16.	Duration
17.	Modification to Contract
18.	Performance Security
19.	Eligibility & Evaluation Criteria
20.	Technical Evaluation criteria (Annexure 1)
21.	Financial Evaluation (As per Annexure 2)
22.	Scope of Work:
23.	Bill of Quantity (As per Annexure 6 & 7)
24.	Warranty Services
25.	Documentation
26.	Service Level Agreement:
27.	Payment Schedule:
27.1.	Payment Schedule for Phase – 1
27.2.	Payment Schedule for Phase – 2
27.3.	Payment Schedule for Phase – 3
27.4.	Payment Schedule for Phase – 4 (Final Settlement)
28.	Penalty
29.	Indemnity
30.	Termination, Dispute Resolution & Other
	Page 2 of 44

30.1.	Termination of Contract	
30.2.	Force Majeure	
30.3.	Notices	25
30.4.	Resolution of Disputes	20
30.5.	Applicable Law	
ANNEXURE	-1	21
ANNEXURE	3	24
ANNEXURE	4	25
ANNEXURE	5	25
ANNEXURE	6	29
ANNEVIDE	7	Frank Bookmark not defined

Government Polytechnic Sheohar

Page 3 of 44

Ritor Pier.

1. Abbreviations and Definitions

Abbreviations	Descriptions			
AP	Access point			
DSTTE	Department of Science, Technology and Technical Education			
DSC	Digital Signature Certificate			
EMD	Earnest Money Deposit			
FAT	Final Acceptance Test			
GST	Goods & Service Tax			
INR	Indian Rupees			
IP	Internet Protocol			
LOI	Letter of Intent			
LAN	Local Area Network			
NIT	Notice Inviting e-Tender			
PBG	Performance Bank Guarantee			
PAN	Permanent Account Number			
PSU	Public Sector Undertaking			
SLA	Service Level Agreement			
UOM	Unit of Measures			

Page 4 of 44

2. Notice Inviting Tenders

- 1. Government Polytechnic Sheohar has been constituted under the Department of Science, Technology and Technical Education, Government of Bihar to cater to the needs of technical education. The Government Polytechnic Sheohar intends to invite bids from eligible entities Onboarding Service Provider for LAN & Wi-Fi networking and augmenting with the existing network in the institute Premises as mentioned in the tender document.
- 2. The contract will be signed between Principal, Government Polytechnic Sheohar and the successful agency/bidder.
- 3. To participate in the e-tendering process, the bidder/agency are required to get themselves registered with eproc2.bihar.gov.in.

4. Schedule of Events:

Sn.	Event Description	Timeline		
4.1	Last date & time of downloading the RFP	Till 25.09.2024 up to 05:00 PM, on eproc2.bihar.gov.in		
4.2	Pre-bid meeting (if required)	14.09.2024 at 11:30 AM		
4.3	Submission (upload) of online bidding document.	Till 25.09.2024 up to 05:00 PM, on eproc2.bihar.gov.in		
4.4	Submission of EMD	Offline by Demand Draft to Principal, Government Polytechnic Sheohar		
4.5	Submission of Tender Documents in Hardcopy/Original	Till 27.09.2024 at 05:00 PM at GP Sheohar Office		
4.6	Opening of Technical Bid	28.09.2024 on the eproc2.bihar.gov.in		
4.7	Opening of Financial Bid	30.09.2024 on the eproc2.bihar.gov.in		
4.8	Pre- bid meeting venue	Government Polytechnic Sheohar, At- Parihara, P.O Chamanpur, P.S Piprahi, Dist Sheohar (Bihar), Pin- 843329		
1.9	Contact person	Principal, Government Polytechnic Sheohar Mobile no - 9470252143 Email ID- principal.gpsheohar d.gmail.com Nodal Officer, Government Polytechnic Sheoha Mobile no - 7992234530 Email ID- er.ashu26@gmail.com		
.10	Method of Selection	Least Cost Selection (LCS)		

Note

- i.) Interested bidders may obtain further information about this Notice Inviting Tender (NIT) from the office of Government Polytechnic Sheohar .
- ii) No tender will be accepted after closing date and time in any circumstances.
- 5. Bidder may also download the tender document available from eproc2.bihar.gov.in_and submit the tender by using the downloaded document.
- 6. The Government Polytechnic Sheohar will select the bidder based on Least Cost Selection (LCS) method for Onboarding Service Provider for LAN & Wi-Fi networking and augmenting with the existing network in the Institute Premises.
- 7. The tender shall be accompanied by Earnest Money Deposit (EMD) of Rs. 25,000/- (Twentyfive thousand rupees only) in the shape of Demand Draft from any Schedule Bank in favour of Principal, Government Polytechnic Sheohar .

Page 5 of 44

- Principal Government Polytechnic

Sheohar

- 8. The technical and financial bids must be submitted through eproc2.bihar.gov.in before the date and time specified in the tender document. The Government Polytechnic Sheohar doesn't take any responsibility for the delay / Non-Submission of Tender / Non-Reconciliation of online Payment caused due to Non-availability of Internet Connection, Network Traffic/Holidays, or any other reason.
- The bidders shall submit their eligibility and qualification details, Certificates as mentioned in the tender document, in the online standard formats given in eproc2.bihar.gov.in at the respective stage(s) only.
- 10. The bidders shall upload the scanned copies of all the relevant certificates, documents etc., in support of their eligibility criteria / technical bids and other certificate /documents in the eproc2.bihar.gov.in.
- 11. The bids must be uploaded (e-mode/online) at the eproc2.bihar.gov.in.
- 12. All prospective bidders may attend the Pre-Bid meeting. The venue, date and time are indicated in Schedule of Events as in above section 4.
- 13. The Earnest Money should be deposited on or before the closing date & time indicated above in the Government Polytechnic Sheohar, failing which the tenders will be treated as late tender and would be summarily rejected. Proof of the same shall be uploaded on the eproc2.bihar.gov.in_during the bid submission.
- 14. In the event of any of the above-mentioned dates being declared as a holiday/ closed day for the Government Polytechnic Sheohar the tenders/EMD will be opened/received on the next working day at the scheduled time.
- 15. Government Polytechnic Sheohar reserves the right to accept or reject any or all tender or change the terms and condition of NIT or cancel the NIT without assigning any reasons at any stage and time.
- For further enquiry and information, contact the following officer during office hours 10:00
 AM to 05:00 PM- Contact No--.9470252143
- 17. All further notifications/Corrigendum/Addendum if any shall be posted on eproc2.bihar.gov.in.
- 18. When reading this document if you identify any errors or omissions, please advise Principal, Government Polytechnic Sheohar in writing, in 5 calendar days, giving a brief description of the problem, its location within document and your contact details.

Confidentiality

This document contains privileged and confidential information pertaining to the "Onboarding Service Provider for LAN & Wi-Fi networking and augmenting with the existing network in the Institute Premises" at Government Polytechnic Sheohar . The access level for the document is specified above. The addressee should honour access rights by preventing intentional or accidental access outside access scope.

Principal/ Principal In charge Government Polytechnia Sheohar

Government Polytechnic
Sheohar

Page 6 of 44

Riter Pita

Instruction to Bidders

- a. Government Polytechnic Sheohar Invites proposals from experienced and eligible service provider for LAN & Wi-Fi networking and augmenting with the existing network in the Institute Premises (All Academic, Examination Hall, Auditorium, Administrative, Residential, Hostel Blocks, outdoor open area etc.) of the Institute campus.
- b. The bidder shall submit his bid/tender on eproc2.bihar.gov.ln.
- c. The bidder may use their Digital Signature Certificate (DSC) if they already have. They can also take Digital Signature Certificate (DSC) from any of the authorized agencies.
- d. For user-id they must get registered themselves on eproc2.bihar.gov.in and submit their bids online. Offline bids shall not be entertained by the Tender Inviting Authority (TIA).
- e. Bids not submitted, as per the above Performa / Instructions mentioned in this RFP document, will be summarily rejected.
- The bidders shall submit their eligibility and qualification details, technical bid, financial bid, etc., in the online standard formats given on eproc2.bihar.gov.in.
- g. The bidders shall upload the scanned copies of all the relevant certificates, documents etc. with indexing and paging, in support of their eligibility criteria / technical bids and other certificates /documents on the eproc2.bihar.gov.in.
- h. The bidder shall digitally sign the supporting statements, documents, certificates, uploaded by him, owning responsibility for their correctness/authenticity. The bidder shall attach all the required documents for the specific tender after uploading the same during the bid submission as per the tender notice and bid document.
- The rate quoted by the bidder shall remain same throughout the contract period including any extension thereon. No increment in rates would be permitted in any circumstances.
- The Bidder is obliged to work closely with Government Polytechnic Sheohar act within its own authority and abide by directives issued by Government Polytechnic Sheohar from time to time.
- k. All the required documents should be attached at the proper place and with proper nomenclature (as mentioned in the e-forms) otherwise the tender of the bidder will be rejected.
- The bid (technical and financial details of the bidder) shall be submitted on or before the last date of submission in online mode only. Tenders submitted after the stipulated date & time (closing date and time for uploading the tender and submission of EMD as mentioned in Clause 4, Notice Inviting Tender (NIT)) shall not be considered and would summarily be rejected.
- m. The decision of Principal, Government Polytechnic Sheohar in regard to interpretation of the Terms & Conditions and the Agreement shall be final and binding on the bidder.
- n. In case of any disputes on execution of the work during the period of contract, the decision of the principal, Government Polytechnic Sheohar shall be binding and final, agreeable in full by both the parties. Any legal disputes shall be subject to Bihar jurisdiction.
- o. Any change/corrigendum/extension of closing/ opening dates in respect of this RFP shall be issued through website only and no press notification will be issued in this regard. Bidders are therefore requested to regularly visit Government Polytechnic Sheohar (https://www.gpsheohar.ac.in/) for updates.
- p. All available technical literature, catalogues, and other data in support of the specifications and details of the items should be furnished along with the offer.
- q. Samples of any product, if called for, should be submitted free of all charges by the tenderer and purchaser shall not be responsible for any loss or damage thereof due to any reason whatsoever. In the event of non-acceptance of tender, the tenderer will have to remove the samples at his own expenses.
- r. Equipment's offered should strictly conform to the specifications. The tenderer should also indicate the Make/Type number of the equipment's offered and provide catalogues, technical

Page 7 of 44



literature, and sample, whatever necessary along with the quotation. Test certificates wherever necessary should be forwarded along with supplies.

- s. The bidder will be liable to replace if any hardware faulty during the contract period without any extra cost during the warranty period.
- t. The bidder has to arrange necessary insurance coverage to the workmen/machines/equipment's etc deployed by him and shall arrange necessary safety measures before starting the work.
- u. In the case of more than one Bidder has quoted same minimum price the bid shall be evaluated through a lottery system and the videography of the complete process shall be kept as a record (as per order no 2988, dated 24.03.2023 of the Department of Finance, Government of Bihar -Annexure -5).
- 4. Inspection of Site and Equipment

The Bidders are advised to physically visit and inspect, all the existing networking facilities, building and premises as such, etc. that may be necessary for preparing the bid and for entering into an agreement for the execution of the project. The bidder should take into account of all existing infrastructure available with the Institute during preparation of the bid. Bidder at its own expense should survey the site. No complaints of any nature would be entertained later.

Tendering Expense

The bidder shall bear all costs and expenditure incurred and/or to be incurred by it in connection with its tender including preparation, mailing and submission of its tender and subsequently processing the same. The Government Polytechnic Sheohar shall in no case be responsible or liable for any such cost, expenditure etc. regardless of the conduct or outcome of the tendering process.

- 6. Right to Accept Any Offer and to Reject Any or All Offers Government Polytechnic Sheohar reserves the right to accept or reject any tender offer, and to terminate the tendering process and reject all tenders at any time prior to award of contract, without thereby incurring any liability to the affected vendor(s) or any obligation to inform the affected vendor(s) of the grounds for such action.
- Language of the tender The tender submitted by the bidder and documents relating to the tender shall be written in the English language only.
- 8. Taxes

The Bidders shall fully familiarize themselves about the applicable domestic taxes (such as GST, income taxes, duties, fees, levies, etc.) on amounts payable by the Purchaser under the resultant Agreement. All such taxes must be included by Bidders in the financial proposal.

9. Concessions permissible under statutes

The Bidders while quoting against this tender, must take cognizance of all concessions permissible, if any, under the statutes and ensure the same is passed on to the purchaser, failing which it will have to bear extra cost. In case Bidder does not avail concessional rates of levies like customs duty, excise duty, Cess etc. Government Polytechnic Sheohar will not take responsibility towards this.

10. Amendments to Tender Documents

At any time prior to the deadline for submission of tenders, the Government Polytechnic Sheohar may, for any reason deemed fit by it, modify the tender document/s by issuing suitable amendment(s) to it. Such an amendment will be notified on Government Polytechnic Sheohar

Page 8 of 44

website (https://www.gpsheohar.ac.in/) and the same shall be binding to all prospective bidders. Government Polytechnic Sheohar will not issue any separate communication in this regard.

11. Pre-Bid Meeting

To provide response to any doubt regarding terms and conditions, scope of work and any other matter given in the tender document, a pre-bid meeting has been scheduled to be held in the office of Government Polytechnic Sheohar or an online meeting may be scheduled. The clarification sought by representative of prospective bidders shall be responded appropriately. However, they shall clarify and will be asked to submit their written request by close of office next working day. The Government Polytechnic Sheohar shall upload written response on the Government Polytechnic Sheohar (https://www.gpsheohar.ac.in/) website to such requests for clarifications, without identifying its source. In case required, amendments issued, shall be binding on all prospective bidders. Further, the issue raised having been clarified shall be final. Bidders are advised to visit the Government Polytechnic Sheohar (https://www.gpsheohar.ac.in/) website regularly for any updates/ corrigendum/ amendments etc.

12. Earnest Money Deposit (EMD)

- a) The tender shall be accompanied by Earnest Money Deposit (EMD) of 25000/- (Twenty-five thousand rupees only) in the shape of Demand Draft from any Schedule Bank in favour of Principal, Government Polytechnic Sheohar must be submitted offline, as per the terms and conditions mentioned in this document. EMD should not have been issued on a date later than the last date for submission of bidding document i.e., 27/09/2024.
- b) The EMD of unsuccessful bidder will be returned to them without any interest, after execution of the contract. The EMD of the successful bidder will be returned without any interest, after receipt of performance security as per the terms of contract.
- c) The EMD shall be forfeited by Government Polytechnic Sheohar hereunder or otherwise, under the following conditions:
 - If a bidder engages in a corrupt practice, fraudulent practice, coercive practice, undesirable practice, or restrictive practice.
 - If a bidder withdraws its bid during the period of bid validity as specified in this Tender and as extended by the Government Polytechnic Sheohar from time to time.
 - In the case of selected bidder, if it fails within the specified time limit:
 - i. to sign the contract and/or
 - to furnish the Performance Security (PS), before signing the contract agreement, within the period prescribed in the Letter of Intent (LoI).

13. Bid Validity

The submitted bids shall remain valid for a period of 180 days after the date of submission.

14. Licensing

The Implementing Agency will follow the following licensing conditions:

a) The bidder shall procure the licenses of the third-party software wherever applicable/ required in accordance with its procedures by payment of applicable license fees on behalf of Government Polytechnic Sheohar. The licenses thus procured would be in the Government Polytechnic Sheohar. The bidder shall ensure that third party vendors provide standards-based customer interface and considers other factors like regular updates and support etc. The Bidder should provide adequate licenses for all the modules mentioned in the scope so that all users can access their respective functionalities as per their role without any constraints.

Page 9 of 44

Government Polytochale

Sheohar

- All licenses should be either supported by OEMs/subscription providers for entire contract period.
- c) All the aforesaid products should have a roadmap for updates and patch management either from OEM or Subscription provider and providing the same would be the responsibility of the bidder for the contract period.

15. Signing of the Contract

The Contract document/Agreement between Government Polytechnic Sheohar and selected bidder should be executed within 21 days of the issue of the Letter of Intent (LoI). The selected bidder will have to submit the Performance Security (PS), as applicable before signing of the agreement. Non-fulfilment of this condition will result in cancellation of the award and forfeiture of the EMD with consequential action if so desire.

16. Duration

The contract, if awarded, shall be valid for a period of one year from the date of award. In case of breach of contract or in the event of not fulfilling the minimum requirements/ statutory requirements, Government Polytechnic Sheohar shall have the right at any time to terminate the contract forthwith in addition to forfeiting the Performance Security amount deposited by the bidder and initiating administrative actions for blacklisting, etc.

17. Modification to Contract

The contract when executed by the parties (Government Polytechnic Sheohar and the bidder) shall constitute the entire contract between the parties (Government Polytechnic Sheohar and the bidder) in connection with the services and shall be binding upon the parties (Government Polytechnic Sheohar and the bidder). Modification, if any, to the contract shall be in writing and with the consent of both the parties (Government Polytechnic Sheohar and the bidder) and not otherwise.

18. Performance Security

- a. The successful bidder shall have to furnish a performance security equivalent 5% of the Project cost, in the shape of a Bank Guarantee issued by a scheduled Bank in favour of Principal, Government Polytechnic Sheohar. The Bank guarantee shall be as per proforma at "Annexure 3" and remain valid for a period, which is six months beyond the date of expiry of the contract. The Performance Security will be returned to the bidder, upon validation of completion of all contractual obligations including warranty.
- The performance security should be submitted before executing the contract /signing of the contract document positively.
- c. If the bidder violates any of the terms and conditions of tender document of this Notice Inviting Tender/Tender in any manner, the Performance Security shall be liable for forfeiture, wholly or partly, as decided by the Government Polytechnic Sheohar and the contract may also be cancelled/terminated. Further, the bidder may be blacklisted for a reasonable period as decided by the Department of Science, Technology and Technical Education/ Government Polytechnic Sheohar.

19. Eligibility & Evaluation Criteria

This invitation is open to organisation who fulfil the eligibility & qualification criteria specified here under.

Page 10 of 44



Sn	Eligibility Criteria	Mandatory Documents to be submitted by the bidders
1	The Bidder should be an established entity registered under Companies Act 1956/2013 or Partnership Act 1932 or Limited Liability Partnership Act 2008 or Proprietorship Firm/ Government Organization/ Public Sector Undertaking.	 For Company- Copy of the Certificate of Incorporation issued by the Registrar of Companies (RoC) under companies act 1956/2013.
2	The bidder should have a registered office / Branch Office for operational support in the state of Bihar.	Documentary evidence
3	The Bidder must have average annual turnover of not less than INR 1 Crore in last three financial year. (FY 2020-21, FY 2021-22 & FY 2022-23)	Audited Balance sheet and Profit & Loss Account for last 3 financial year (FY 2020-21, FY 2021-22 & FY 2022-23)
4	The bidder must have at least 3 years'	Workorder/Purchase Order along with Payment receipt
	Number of Project Experience in V	Workorder/Purchase Order along with Payment receipt

Page 11 of 44

6	The Bidder should have Manufacturers	Bidder has to provide an Ink Signed
	authorization and a direct back-to-back	Manufacturer's Authorization Form (MAF)
	support agreement with the OEM for	from the OEM
	the equipment. The Support agreement should include the activities like	
	Technical Assistance support, Spares	
	support etc. Submit supporting	
	documents for same	
7	The bidder must not be blacklisted by a	Self-declaration (As per annexure 4)
	Central / State / Local Government	
	Organization / Institution / PSU	
8	Bidder Must have ISO 9001, 20000 and	Certificate Attached
	27001 Certificates	

Note: Bidder shall ensure compliance to Land Border Clause including amendments thereon. Self-declaration as per the clauses mentioned in Land Border Clause. Noncompliant bid(s) will be summarily rejected.

20. Technical Evaluation criteria (Annexure 1)

Criteria	Details	Marks	Details	Marks
Number of Project Experience in- installation, commissioning, and maintenance / LAN & WI-FI Network Services and associated software for a Central / State Government Organization / Public Sector Unit (PSU)/ Private University Recognized /affiliated to UGC/ AICTE in India. With a minimum contract value of 5 lakh	2 Projects	10	=>3 projects	20
Average turnover of the company=: in the last 3 years (FY 2020-21, < FY 2021-22 & FY 2022-23)		10	=>1.5 crore	20
Bidder's experience in- installation, commissioning, and 5 maintenance / LAN & WI-FI Network Services and associated software with Central / State Government Organization / Public Sector Unit (PSU)/ Private University Recognized /affiliated	3Years & < years	10	> 5 yrs.	20
Total				60

Note: Bidders score 50% or more i.e., 30 marks or more, shall qualify for the financial evaluation.

Page 12 of 44

21. Financial Evaluation (As per Annexure 2)

Financial bids shall be opened only for the vendors whose bids are found to be Technically fit/ substantially responsive and complying with minimum eligibility criteria.

- i) Government Polytechnic Sheohar will open the financial bids of only Technically Qualified bidders as per eproc2.bihar.gov.in.
- ii) Discrepancy in the financial bid, it will be dealt as per the following:
 - a. If there is an error in a total corresponding to the addition or subtraction of subtotals, the subtotals shall prevail, and the total shall be corrected.
 - b. If there is a discrepancy between words and figures, the amount in words shall prevail.
- iii) Of all the Financial Bids opened, the bidder whose financial bid is lowest (hereby referred to as L1 bidder) will be considered eligible and award of contract.
- iv) In the case of more than one Bidder has quoted same minimum price the bid shall be evaluated through a lottery system and the videography of the complete process shall be kept as a record (as per order no 2988, dated 24.03.2023 of the Department of Finance, Government of Bihar - Annexure -5).

22. Scope of Work:

Broad scope of work should be:

To enable the institute premises with networking and Wi-Fi services with augmentation of existing infrastructure, (if available):

- To Set up network & WIFI services inside Institutes premises, which would consist of LAN, optical fibre, Switches, Routers, Wireless Access Points (Indoor and Outdoor), Security equipment (Firewall) etc.
- To provide wired and wireless connection in Admin Blocks, Academic Blocks, Library, Auditorium, Laboratory, Hostels, Classrooms, Examination Hall, etc. also provide internet access through wireless medium to the students, staff, faculty, and guest visitors, as per the requirement of the institute.
- To enable Authentication, Authorization, and Accounting (AAA) security service for controlling and tracking user access both in LAN and Wi-Fi network.
- To install Access Points at suitable location to receive the maximum coverage and has no interference. Access points inside the main building must be covered with a protective mesh that can withstand any human-caused damages.
- · Access Points shall provide seamless coverage within its range as well as between different Access Points of the proposed Wi-Fi Network.
- Each Access point must support minimum of 50 concurrent clients/devices/users.
- · Insure Installation, commissioning, and maintenance of any mounting structure for Access Points like Pole (as per requirement) along with required accessories at each site/location.
- Provide module for keeping a log of Wi-Fi services to be utilized by the end user such as IP details, URL visited, Time stamp, End user Authentication, Mobile No. MAC & IP Address, access time, duration, data consumed, Access pointwise (bandwidth, Download/ Upload Speed) etc. to meet the compliance with all regulatory and legal guidelines issued by DoT/TRAI time to time.
- Provide Solution compliant with applicable guidelines of DoT & TRAI.
- Ensure that all software / firmware etc. should be updated periodically for patches/release

Page 13 of 44

Government Polytechnic

- Solution should be scalable to efficiently support a bandwidth of 1Gbps/2 Gbps or more (as case maybe) as required by Institute in future. A certificate should be given by the bidder in this regard.
- Solution should have capabilities to support separate SSID's and Group Policies for Students,
 Faculty, Staff and Guest Visitors of the Institute with separate time/bandwidth-based policy for all categories.
- Ensuring adherence to the agreed Service Levels and Service Quality for each of the deliverables executed by them.
- Ensure the delivery of equipment and installation of entire network systems at the institute within 8 weeks from the date of award of contract.
- Solution should cater at least 1000 concurrent users at institute level, which should be scalable for future need. Self-declaration should be given by the bidder in this regard.
- Maximum of two devices authenticated per registered user at any point of time.
- Provide solution for the ability to filter the type of content allowed (e.g., blacklist URLs etc)
- The solution must have a Network Management System (NMS) with following features:
 - a) Web based user interface (secured).
 - b) Should support fault, and performance management.
 - c) Ability to present graphical view of the network.
 - d) Capability to view the network topology. The NMS should be able to monitor all the active components, Wired, and Wireless elements, of the network.
 - e) The NMS should have the capabilities to support all the hardware in the existing Network irrespective of OEM.
- Provide appropriate training to the designated/nominated staffs of the institute.
- · Should carry necessary civil and related restoration work etc.
- Provide 24x7 helpdesk for customer support to the end users.

Page 14 of 44

Rites)



23. Bill of Quantity (As per Annexure 6 & 7)

20.	bill of Quantity (As per Almexare o & 7)			
Sn.	Components	Type of Device	иом	Quantit
1	Firewall with minimum 8 numbers of 1G port and 2 Nos of fibre Optic port.		l No's	1
2	Distribution Switch - L3 Switch with 24 SFP ports 2 10GBASE ports 4 10G SFP ports L3 Stackable Managed Switch	Physical	No's	1
3	Access Switch- 24 PoE+ port L2 with minimum 2 SFP (Managed)	Physical	No's	6
4	Access Switch- 16 PoE+ port L2 with minimum 2 SFP (Managed)	Physical	No's	8
5	Access Switch- 08 PoE+ port L2 with minimum 2 SFP (Managed)	Physical	No's	5
6	Indoor AP (With Mounting Kit & Controller) - II	Physical	No's	30
7	Rugged and waterproof Outdoor IP 65 AP (With Mounting Kit)	Physical	No's	4
8	16 U Rack	Physical	No's	1
9	6 U rack (With PDU) inside Gallery	Physical	No's	7
10	CAT6 cable (Per Box 305 meter)	Physical	Box	20
11	IO box for CAT-termination	Physical	No's	102
12	6 Core Fibre with LIU and termination accessories	Physical	Meter	1000
13	LC to LC patch code	Physical	No's	14
14	OFC Patch Panel	Physical	Unit	5
15	RJ 45 Connector	Physical	No's	500
16	Conduit for both electrical & LAN wiring & all required material	Physical	R mtr	3500
17	24 port LAN patch panel	Physical	No's	8
18	UPS (2KVA)	Physical	No's	1
19	Wirless Access Point Controller	Physical	No's	1
20	SFP Module	Physical	No's	16
	NMS a) web base user interface (secured) b) should support fault, and performance management. C) Ability to present graphical view of the network. D) Capability to view the network topology. The NMS should be able to monitor all the active components, wired, and wireless elements, of the netword. e) the NMS should have the capabilities to support all the hardware in the existing network irrespective of OEM.	Software	No's	1
2	Patch cord 2 meter	Physical	No's	200
3	Installation and Commissioning Charge			1

Page 15 of 44



Note:

- The detail specification of the abovementioned components is attached in Annexure-6.
- Prices should be quoted in Indian Rupee only and indicated both in figures and words. The amount mentioned in words will prevail.
- It is bidders' responsibility to install, commission, test, and go live.
- All the items' counts mentioned above is only tentative number, it may exceed or less as per the work.
- The BoQ mentioned in the RFP is for the entire scope of work and duration mentioned in this RFP. Bidders are requested to do site visits to check the feasibility and to ensure achievement of the objective and scope of work of this RFP.

24. Warranty Services

The bidders will provide comprehensive warranty details for all the Hardware/ software. It would be the bidder's responsibility to arrange all updates and upgrades through respective OEMs. The bidder must provide all updates and upgrades for the proposed devices free of cost during warranty period.

The bidder shall put in place all back-to-back support agreements for the proposed network components with respective OEMs for warranty services and submit documents in support of the same.

Note: Warranty support services for all network equipment during the execution of the project before the project is signed off shall be provided by the bidder at no cost to Government Polytechnic Sheohar .

25. Documentation

The Bidder shall provide the following documentation. The content and format of the documentation will be discussed and agreed with Government Polytechnic Sheohar prior to development/delivery of the documentation.

- a) Comprehensive configuration of all devices
- b) Manuals of all devices (hard and/or soft copies).
- c) Back up policy and procedure for various network devices.
- d) Network Monitoring Manual: A comprehensive document on what needs to be monitored daily (or at specified intervals) and how the records to be maintained.
- e) A comprehensive test report covering all the areas.

26. Service Level Agreement:

The purpose of this Service Level Agreement (hereinafter referred to as SLA) is to clearly define the levels of service to be provided by the Bidder to Government Polytechnic Sheohar for the duration of this contract. SLA defines the terms of the Bidder's responsibility in ensuring the timely delivery of the deliverables and the correctness of the same based on the agreed Performance Indicators as detailed in the Agreement.

Page 16 of 44

- Principal Government Polytechnic



Scanned with OKEN Scanner

S. No.	Activity/SLA Parameter	Target Service Level	Penalty on Breach of Service Level
1	Resumption of monitoring and security services	Firewall and related items NMS, Helpdesk solution within 1 day from reporting	, Penalty of INR 5,000/ per
2	Resumption of network services -switches.	Within 24 hours for unserviceability of switches and access points	1
3	Repair of un-serviceable component listed in BoQ.	Within 5 working days	Penalty of INR 5,000 shall be charged per day basis
4	Repair of cut OFC.	Underground OFC – within 48 hours Overground OFC – within 24 hours	Penalty of INR 8,000/ per day shall be charged
5	Response Time	Average Time taken to acknowledge, respond and close once a ticket/incident is logged through one of the agreed channels (like Ticketing solution, Telephone, Email etc.). This is calculated for all tickets/incidents reported within the reporting month. 95% of the incidents should be responded within 15 minutes.	• <95% & >=90%: 2% of the Residual amount (Payment schedule phase 4) • < 90% & >= 85%: 5% of the residual amount (Payment schedule phase 4) • < 85%: 7% of the residual amount (Payment schedule phase 4)
6	Availability of Monthly SLA Reports covering all the above SLA parameters required for monitoring within the defined time	Report of last month shall be submitted by First week of the current month.	Penalty of INR 5,000/- Per month
7	Any Security Breach • Successful hacking of any active component on the network by any unauthorized user. • Any cyber-attack into the network. • Or any other privacy rule is broken as per Govt. of India guidelines or Govt. of Bihar	For any reported security breach	For every security breach reported and proved, there shall be a penalty of INR 50,000/

SLA Monitoring: In the duration of the contract, the selected bidder shall be required to provide the reports for monitoring the SLAs.

Page 17 of 44



- a) The penalty shall be calculated and deducted from residual amount (Payment Schedule phase
- b) All above-mentioned penalties are exclusive to each other.
- c) The maximum penalty at any point of time and for any period should not exceed 25% of residual amount (Payment Schedule phase 4).
- d) Penalties shall not be levied on the successful bidder in case of is a Force Majeure event affecting the SLA which is beyond the control of the successful bidder.
- e) The decision of Government Polytechnic Sheohar regarding interpretation of the Terms & Conditions and the Agreement shall be final and binding on the Bidder.

27. Payment Schedule:

27.1. Payment Schedule for Phase – 1

40 % of the total cost on delivery of material/equipment's -

The Bidder shall submit the invoice along with following documents: -

- a. Physical verification by the Institute supported by Delivery challan/Courier receipt or any other supporting document.
- b. Document clearly mapping list of the materials with Make, Model, Serial number.
- 27.2. Payment Schedule for Phase 2

20% of the total cost – On completion of Supply and installation

The Bidder shall submit the invoice along with following documents: -

- a. Delivery challan signed by competent authority of institutes/sites.
- b. Installation report
- 27.3. Payment Schedule for Phase 3

10% of the total cost - On completion Final acceptance test by the institute, commissioning and Go-Live

The Bidder shall submit the invoice along with following documents.

- a. Site visits for physical check/functionality checks of the commissioned devices/software.
- b. Link commissioning report duly signed off by the competent authority of Institute.
- c. Asset register needs to be submitted along with SOP and other documents.
- d. Training to designated staff of the institute.
- e. Self-declaration by the Bidder
- f. Warranty document form OEM.
- 27.4. Payment Schedule for Phase 4 (Final Settlement)

30% of the total cost would be linked with the SLA which will be paid after deduction of the penalties. The payment terms for the phase-4 shall be mutually agreed by the bidder and Government Polytechnic Sheohar .

28. Penalty

Rites Pita.

The bidder shall ensure the delivery of equipment and installation of entire network systems at the institute within 8 weeks from the date of award of contract. If not completed in the specified timeline suitable penalty would be imposed as decided by the principal of

Page 18 of 44



Government Polytechnic Sheohar .

Indemnity

The supplier shall indemnify, protect, and save Government Polytechnic Sheohar against all claims, losses, costs, damages, expenses, action suits and other proceedings resulting from infringements in respect of all hardware and software supplied to Government Polytechnic Sheohar . Government Polytechnic Sheohar also stand indemnified from any compensation arising out of accidental loss of life or injury sustained by any manpower while working on the project.

30. Termination, Dispute Resolution & Other

30.1. Termination of Contract

- a) If bidder found to be involved in fraudulent practices (misrepresentation or omission of facts or suppression/hiding of facts or disclosure of incomplete facts), in order to secure eligibility to the bidding process during the submission of bid or after release of Letter of Intent (LoI) or agreement formalization after signing of contract, shall be liable for punitive action amounting to blacklisting of the bidder, including the forfeiture of concerned EMD and/or Performance Security also, whatever it relates.
- b) Notwithstanding contained here, the Government Polytechnic Sheohar prejudice to any other contractual rights and remedies available to it, shall by written notice of any default in service / installation/ testing /commissioning etc. sent to the bidder, terminate the contract in whole or in part, if the bidder fails to perform services as specified in the present contract read with the terms of the contract agreement or any other contractual obligations within the time period specified in the contract and the firm may be blacklisted, consequently the performance security may be forfeited.
- c) Termination for Insolvency If the bidder becomes bankrupt or otherwise insolvent, it will inform to the Government Polytechnic Sheohar within 30 days written notice to terminate the contract. Government Polytechnic Sheohar reserves the right to terminate, without any compensation, whatsoever, to the bidder, and may forfeit the performance security.
- d) Termination by mutual consent In the event the Government Polytechnic Sheohar and the bidder mutually agrees to the terminate the contract, either party shall give 90 days' written notice to the other party and after the consent of both the parties contract may be terminated without any Legal or financial obligation on any party to the contract.

30.2. Force Majeure

- a) For purposes of this clause, Force Majeure means an event beyond the control of the bidder and not involving the bidder's fault or negligence, and which is not foreseeable and not brought about at the instance of, the party claiming to be affected by such event and which has caused the non - performance or delay in performance. Such events may include wars or revolutions, hostility, acts of public enemy, civil commotion, sabotage, fires, floods, explosions, earthquake, epidemics, quarantine restrictions, strikes excluding by its employees, lockouts excluding by its management, and freight embargoes.
- b) If a Force Majeure situation arises, the bidder shall promptly notify the Government Polytechnic Sheohar in writing of such conditions and the cause thereof within 7 days of occurrence of such event. Unless otherwise directed by the bidder in writing, the bidder shall continue to perform its obligations under the contract as far as reasonably practical

Page 19 of 44



and shall seek all reasonable alternative means for performance not prevented by the Force

c) If the performance in whole or in part or any obligation under this contract is prevented or delayed by any reason of Force Majeure for a period exceeding thirty days, either party may at its option terminate the contract without any financial repercussion on either side.

30.3. Notices

Notice, if any, relating to the contract given by one party to the other, shall be sent in writing or e-mail or by post. The addresses of the parties for exchanging such notices will be the addresses as incorporated in the contract between the Government Polytechnic Sheohar and the bidder.

30.4. Resolution of Disputes

- a) Any dispute, difference, or claim arising out of or in relation to this Agreement, will be settled by reaching a mutual understanding between the parties.
- b) If any further dispute arises between the parties thereupon, the same will be settled as per the extant law of land through the competent court of law under the territorial jurisdiction of Sheohar only.

30.5. Applicable Law

The contract shall be governed by and interpreted in accordance with the laws of India for the time being in force.

> Principal ... Government Polytechnic Sheohar

Page 20 of 44

<Company Letter head>

TECHNICAL DATA SHEET

Details of contractor/ service provider

S.I No.	Description		Information	
1	Name of Tenderer & Contact personaddress, email & mobile No: -	on with complete		
2	Status of the Tenderer (attach documents if registered company / partnership / proprietorship / LLP) with year of establishment.			
3	Statutory details (photocopy to be a) Registration No. of the Firm-b) PAN-c) GST Reg. No			
4	Number of Project Experience in S / establishment of network conne Public Sector Unit (PSU)/ Private India. With minimum contract val	ectivity for a Centre University Recog	al / State Governi gnized /affiliated	ment Organization to UGC/ AICTE in
	Name of the Project		Client Name & Contact information	Project Value (INR)
	1. 2. 3.			
5	Average turnover of the company FY 2020-21	in the last 3 years FY 2021-22	FY 2022-23	
6	The bidder must have at least 3 ye commissioning, and maintenance vector Unit (PSU)/ Private University	with a Central / Sta	ate Government O affiliated to UGC	rganization / Public
	Name of the Project		Client Name & Contact information	Duration (Year)
	1. 2. 3.			
7	Declaration that the bidder has not been debarred / blacklisted by any Government/Semi-Government/PSU (As per Annexure 4)			
8	Self-declaration as per the clause	es mentioned in		

Note: Attach necessary documentary evidence to substantiate information mentioned above.

< Authorised Signature >

Name:

Designation:

Page 21 of 44



<Company Letter head>

FINANCIAL BID FORMAT (Rs in Lakh) To,

Principal,

Government Polytechnic Sheohar,

Sn.	Components	Make	Model	Quantity	Amount (A)	GST/Tax amount (B)	Total Amount (C=A+B)
1	Firewall with minimum 8 numbers of 1G port and 2 Nos of fibre Optic port.			1		,	
2	Distribution Switch - L3 Switch with 24 SFP ports 2 10GBASET ports 4 10G SFP ports L3 Stackable Managed Switch			1			
3	Access Switch- 24 PoE+ port L2 with minimum 2 SFP (Managed)			6			
4	Access Switch- 16 PoE+ port L2 with minimum 2 SFP (Managed)			8			
5	Access Switch- 08 PoE+ port L2 with minimum 2 SFP (Managed)			5			
6	Indoor AP (With Mounting Kit & Controller) - II			30			
7	Rugged and waterproof Outdoor IP 65 AP (With Mounting Kit)			4			
8	16 U Rack			1			
9	6 U rack (With PDU) inside Gallery			7			
10	CAT6 cable (Per Box 305 meter)			20			
11	IO box for CAT-termination			102			
12	6 Core Fibre with LIU and termination accessories			1000			
13	LC to LC patch code			14			
14	OFC Patch Panel			5			
15	RJ 45 Connector	+1		500			
16	Conduit for both electrical & LAN wiring & all required material			3500			
17	24 port LAN patch panel			8			

Page 22 of 44

RHO DE

18	UPS (2KVA)	1 1	
19	Wirless Access Point Controller	1	
20	SFP Module	16	
21	NMS a) web base user interface (secured) b) should support fault, and performance management. C) Ability to present graphical view of the network. D) Capability to view the network topology. The NMS should be able to monitor all the active components, wired, and wireless elements, of the netword. e) the NMS should have the capabilities to support all the hardware in the existing network irrespective of OEM.	1	
22	Patch cord 2 meter	200	
23	Installation and Commissioning Charge	1	

Quoted Price: Total Amount (C=A+B) (< Price in Word and Figure>) Note: -

- Prices should be quoted in Indian Rupee only and Indicated both in figures and words. The amount mentioned in words will prevail.
- It is bidders' responsibility to install, commission, test, and go live. Any other cost for accessory or any
 other sundry items needed for installation would be borne by the Bidder only.
- All the items' counts mentioned above is only tentative number, it may exceed or less as per the work.
- The BoQ mentioned in the RFP is for the entire scope of work and duration mentioned in this RFP.
 Bidders are requested to do site visits to check the feasibility and to ensure achievement of the objective and scope of work of this RFP.
- Make & Model are mandatory.

•	<authorised signature=""></authorised>	Name:	Designation:
			0

Page 23 of 44

Rites Dit.



Format for Performance Bank Guarantee Ref: Bank Guarantee No: Date: To

Principal,

Government Polytechnic Sheohar,

Against contract vide Advance Acceptance of the Tender No. Dated covering "RFP for Onboarding Service Provider for LAN & Wi-Fi Networking and Augmenting with the existing network in the Premises of the Institute Premises under Department of Science, Technology and Technical Education, Government of Bihar" (hereinafter called "the Bid"). (hereinafter called the said 'contract') entered into between Government Polytechnic Sheohar (hereinafter called the Purchaser) and M/s. , a Company incorporated under the 1956/2013 or Partnership Act 1932 or Limited Liability Partnership Act Companies Act, 2008 or Proprietorship Firm/ Government Organization/ Public Sector Undertaking and having its Registered Office at(hereinafter called the Bidder) this is the request of the Bidder we (name of to certify that at Branch a body corporate constituted under the Banking Companies [Acquisition and Transfer of Undertakings] Act, 1970 and having its, Registered Office at...... and a branch office atare holding in trust in favour of the Purchaser, an amount of Rs (Rupees only) to indemnify and keep indemnified the Purchaser against any loss or damage that may be caused to or suffered by the Purchaser by reason of any breach by the Bidder of any of the terms and conditions of the said contract and/or in the performance thereof. We agree that the decision of the Purchaser, whether by any breach of any of the terms and conditions of the said contract and/or in the performance thereof has been committed by the Bidder and the amount of loss or damage that has been caused or suffered by the Purchaser shall be final and binding on us and the amount of the said loss or damage shall be paid by us forthwith on demand and without demur to the Purchaser.

- 1. We (Name of the Bank /Branch) further agree that the guarantee herein contained shall remain in full force and effect during the period that would be taken for satisfactory performance and fulfilment in all respects of the said contract by the Bidder i.e. till hereinafter called the said date and that if any claim accrues or arises against us (Name of the Bank /Branch) by virtue of this guarantee before the said date, the same shall be enforceable against us(Name of the Bank/Branch) notwithstanding the fact that the same is enforced within six months after the said date, provided that notice of any such claim has been given to us(Name of the Bank/Branch) by the Purchaser before the said date. Payment under this guarantee shall be made promptly upon our receipt of notice to that effect from the Purchaser.
- 2. It is fully understood that this guarantee is effective from the date of the said contract and that we...... (Name of the Bank /Branch) undertake not to revoke this guarantee during its ourrency without the consent in writing of the Purchaser.
- 3. We undertake to pay to the Purchaser any money so demanded notwithstanding any dispute or disputes raised by the Bidder in any suit or proceeding pending before any court or Tribunal relating thereto our liability under this present bond being absolute and unequivocal.

Page 24 of 44

- 4. The payment so made by us under this bond shall be a valid discharge of our liability for payment there under and the Bidder shall have no claim against us for making such payment.
- (Name of the Bank / Branch) further agree that the Purchaser shall have the fullest liberty, without affecting in any manner our obligations hereunder to vary any of the terms and conditions of the said contract or to extend time of performance by the Bidder from time to time or to postpone for any time or from time to time any of the powers exercisable by the Purchaser against the said Bidder and to forebear or enforce any of the terms and conditions relating to the said contract and we, (Name of the Bank / Branch) shall not be released from our liability under this guarantee by reason of any such variation or extension being granted to the said Bidder or for any forbearance by the Purchaser to the said Bidder or for any forbearance and or omission on the part of the Purchaser or any other matter or thing whatsoever, which under the law relating to sureties, would, but for this provision have the effect of so releasing us from our liability under this guarantee.
- 6. This guarantee will not be discharged due to the change in the constitution of the Bank or the Bidder. Notwithstanding anything contained herein:
 - a. Our liability under this Guarantee shall exceed of Rs.....(Rupees in words only).
 - b. The Bank Guarantee shall be valid up to; and;
 - c. We...... (Name of the Bank / Branch) are liable to pay the guaranteed amount or any part thereof under this Bank Guarantee only and only if you serve upon us a written claim or demand on or before ##.....

Authorised Signatory of the Bank Signature

Full Name/designation/ Address of the official and date WITNESS NO. 1 Signature

Full Name/designation/ Address WITNESS NO. 2 Signature

Full Name/designation/ Address

Page 25 of 44

Format for Declaration by the bidder for not being Blacklisted/ Deb	MANEXURE 4
(To be executed on a non-judicial stamp paper of appropriate stam) Date:	parred:
of Bihar)	p duty (as per Stamp Act
	7.00
To,	
Principal,	
Government Polytechnic Sheohar,	
20. Commonwealth States and Mary	
Subject: Submission of	
Subject: Submission of proposal in response to	the or
Ref: Tender No.:	the Tender for
Dear Sir,	
, authorized representation	
, authorized representative of, hereby sole	emply confirm that the
debarred/ declared ineligible / declared baying discretif	acklisted / homest /
debarred/ declared ineligible / declared having dissatisfactory performent of Bihar/ Any other State Government/ Court	mance and not be
by the Government of Bihar/ Any other State Government/ Government Department, Public Sector Undertails	trance and not banned
ncludes any Government Department, Public Sector Undertaking Statutory Department formed by the Government Local Region in	of the Country
Statutory Department formed by the Government, Local Bodies in institutions in the State, Universities and Societies formed by the Government.	the State Covernment,
nstitutions in the State Universities and Section 1	the State, Co-operative
os on last date of submission of the Bid. In the event of any devinted in	ernment for any reason
nformation/ declaration, Government Polytechnic Sheohar reserved or terminate the Contract without any compensation to the Contract without without any compensation to the Contract without without any compensation to the Contract without	ation from the factual
Bid or terminate the Contract without any compensation to the Comp	s the right to reject the
	pany.
ours faithfully,	
:Authorized Signatory >	
lame:	
Pesignation:	
address:	
elephone & Fax:	
	ANNEXURE 5
	52-44-44/m/2553170/2577 25V
Page 26 of 44	
	~ _
	(AD

निर्धन तस्या पी0री0-40



बिहार गजट

असाधारण अंक बिहार सरकार द्वारा प्रकाशित

3 चैत्र 1945 (श0)

(सं0 पटना 251) पटना. शुक्रवार. 24 मार्च 2023

सं० एम 4 06/2023/2988/वि०,

वित्र विमाग

23 मार्च 2023

शिष्य >> आउटरोसिंग के गाय्यम से मानव बल की सेवाएँ प्राप्त करने एवं पारिश्रमिक मुगतान हेतु प्रक्रिया निर्धारण के सम्बन्ध में ।

ानमारण के साम्बन्ध गृह सम्बन्ध गृह सम्बन्ध विभागों स्वीति विभागों एवं विभागों स्वीति विभागों एवं विभागों साम्बन्ध विभागों साम्बन्ध के आधार पर विभिन्न बनार के मानव बन की संवाई जात की का रही है . इस ज्ञान में विभिन्न विनागों हारा आउटकीसिंग का मान्यम से मानव बन की सदा प्रात्त करन की ज़िल्या में सवा चुनक की तर का संबंध में किन विभाग से परावर्ष की अनेशा की जा रही है।

- 2. ऐसा पाना जा रहा है कि इस प्रकार की निविध के जन में कई निविधानकों आहा निविध प्राप्त करने हैं कुनतम मानी के तम में रखा शुक्त की अस्परवादिक पर (प्रथा, 100 तमन सामी कान) अधित कर दिया जाता है। इस प्रकार के दर का शुक्रमाव सका में रह मानद मन के पारिश्रमिक पर प्रकार है, वर्षीकि एसी स्थिति में एजेंन्सी भाग समा शुक्र की परमाई हुई अनुविध तरीक अन्तान की संभावना गरती है।

 3. एसी स्थिति में सहा शुक्र की पर के साथ-साथ आउटकारिया सामा मानद मान के प्रकार मानिश्रमिक एवं अन्य वेश्वनिक प्रवार को मुनतान सरमान मुनतान सरमान होति है।
- 3. एसी स्थिति में सेटा शुन्क की पर क साध-साध आउटसासिंग से बात मानव मन के स्वतन्त सरिव्यम्भिक एवं अन्य वेशानिक त्यारा का मुनतान सस्याय सुनिश्चित कराये जाने देतु प्रक्रिया एवं तिशा-निप्तत निर्धाति किया जाने की आवश्यकरा। है। दिन मंत्रास्त्र, स्थय प्रभाग, भारत सरकार के Office Memorandum संख्या-F.6 / 1 / 2023-PPD तिर्माक⇔06.01.2023 द्वारा आउटसीसिंग के आवार कर मानव मन की सदाई प्राप्त करने देतु संश शुक्क की स्थानदम् एवं अधिकास पर निर्धारित की गई है।
- सम्प्रक विद्यारीवर्गत आउटस्मिसिंग वा आधार पर मानव बस की सूबा प्राप्त करन केंद्र सदा गुम्क की दर एवं ऐसे मानव बस के पारिश्रमिक का संसमय नुगतान केंद्र विस्तवत प्रक्रिया निर्वाणित की जाती के-

Page 27 of 44

Rites Pia.



- (i) आडटस्वरिंग स मध्यम स पानत क्षत्र की घंडा वाला करने देतु संवा सुक्ता म्युनतय 3.45 प्रतिमत (3 प्रतिमत खान भार 0.45 प्रतिमत संख्यदार मुख्य के नाम में) तथा भविकत्त्व 7 प्रतिमत (संख्यदार मुख्य चित्त) दोगी । इसी भारार पर निविध भार्मित की आसर्थे ।
- (ii) उद्यति निर्धारित न्युनतम् सेया शुन्यां की अधिकीयां से न्युन गुर्व निर्धारित अधिकास्य क्षेत्रा सुख्य की अधिकीयां से उत्तय पर अधिका करने वाले निर्धिताताला की दिलीय निर्धित विकारणीय नहीं होगी । स्था शुन्या का तर य अधिका रूपये में प्रसम्लय के परचात 2 अंक स्थापन अधिका अंक की भजरअंकाज कर दिया जायेगा।
- (iii) निवित्ता य यदि एक से अधिक निविद्यात्राता क्षण उपभूत (Quoted) स्थूनतय सेवा शुक्क की पर समान याई आती है तो केशी स्थिति में औड़री का माध्यम से निवित्ता का निज्यादन दिव्या जायगा तथा इस पूरी प्रक्रिया की विद्यापाली कारायी जायगी । निवित्ता का निज्यादन की पूरी प्रक्रिया में विद्यार दिल निव्यादकी का सुध्यत्त प्रदक्षण अनुष्यक अवस्थित डांगा।
- (iv) मानव बाग क्या ध्रम कंक्याचन विभाग बाग निर्धारित खुनतम मानद्वी एव एक पर कार् वैधानिक नेमता का भुगतान धनिवाची हाता धार इस्ने निविदा (Bid) का भागार नहीं मनावा आया।
- (v) यजनित एजन्मी द्वारा सवा प्रतान पर ग्रंट मानव मन वो प्रतिमार पारिश्विक के पुरातान में श्रम स्वाधन रिनार, विहार सरकार द्वारा श्रमिष्टींका स्वनतम पारिश्विक का पुरातान के अनुपालन किया जाना आवर्षक होता। इसके साथ ही पारिश्विक का पुरातान मानव मन के आधार संबद्ध में के खाता में Real Time Gross Settlement (RTGS) की प्रक्रिया के किया जावरा। पर पुरातान सवा प्राप्त कर ग्रंट विभाग / पाविकार द्वारा आवटसार्थित एजन्मी को गाँव विमुणित की तिथि के तीन कार्य दिवस के अन्दर संविक्ष एजेनी द्वारा किया जावरा। स्वाधित कार्यास्त्र / प्राधिकार द्वारा आवटसार्थित एजेनी वा प्रवच्च मार की हवी तारीख तक प्राप्त दिवस के आसाल में गाँव का पुरातान किया जाना होता। साथ ही सभी वैव्यक्तिक करोती की गाँव का प्रस्त्रम संवीक्ष माधिकार (प्रथा वर्षकारी मदिया निवि संगठन एवं कर्मकारी राज्य वीचा निगम उत्पादि) में आवटसार्थित एजेंसी द्वारा जमा
- (१४) आउटकारिंग एजकी आर कर्षियां / मानव बल वा मायिक पारिश्विक पुगतान (आधार खेच ६ छात में) का साथ्य अगल मार्च वा विषय के साथ उपलब्ध कराया जाना आवश्यक होगा, अध्यक्ष विषय की गति का पुगतान अनुमान्य नहीं होगा। खाध ही वैद्यानिक कहाती / प्रयत्ता (उथा कर्मकर्ती अधिक निर्म हव कर्मकर्ती) गाउट वीमा अंशानान) की गति क्या करने का काश्य सहित क्रमांशिक प्रतिविद्यन भी आउटकार्थित एकंची आर बढ़ा प्राप्त कर पह विभाग / प्रार्थिकार का उपलब्ध कराया जाना आवश्यक होगा।

क्षांचेक:- क्षारेस दिया जाता है कि इस संकल्प की निकार राजपन के क्साचारण कोच में प्रकाशित किया जाय !

विवार गन्यधाल के अवेश में

सोकेच चुन्पर सिंड. राधिय (शंसाधन)।

अधीक्षक, सर्विवालय मुद्रणालय, बिहार, पटना बारा प्रकाशित एवं मुद्रित। बिहार गजट (असाधारण) 251-571+10-बी०टी०पी० Website: http://egazette.bili.nic.in

Page 28 of 44

Government Polytechnic
Sheohar

KHUS PROM



SPECIFICATIONS OF ITEMS MENTIONED IN BOO

SPECIFICATIONS OF ITEMS MENTIONED 1) Firewall with minimum 8 numbers of 1G port and 2 Nos	Compliance (Yes/No)	Remarks
of fibre Optic port.		-
he proposed firewall should not consume more than 1RU Rack-mountable pace.		
The appliance should have multicore processor based architecture.		
The appliance should have minimum 8 x 10/100/1000 Base T Ethernet Port.		
The appliance should have minimum 2 Ports of 10Gbps SFP+ Port.		
The appliance should have minimum 2 x USB 3.0 port and one Console Port		
The appliance Should have minimum 2GB of RAM & 32 GB of more SSD		
Storage from day 0 General Firewall Features		
The Firewall should support BGP,OSPF, RIP v1/v2 routing protocol and IPv4 & IPv6 functionality (Both phase 1 and Phase2).	,	
Solution should support Dead Peer Detection, DHCP Over VPN, IPSec NAT Traversal, Route-based VPN over OSPF, RIP, BGP.		
The Firewall solution should support policy based routing, Application based routing and also Multi Path routing.		
Should support Zero-Touch registration & provisioning using mobile App.		
Proposed solution should have bandwidth quota and time quota for manageability of users.		
solution should support policy based routing, Application based routing and also Multi Path routing.		
Performance & Scalability		
The appliance should have minimum Firewall Throughput of 5 Gbps or better		
The appliance should able to handle minimum 23K new session per second or better		
The appliance should able to handle minimum 3 Gbps Application inspection		
The appliance should have minimum Antivirus/Anti-malware Throughput of 2.5 Gbps or better		
The appliance should have minimum IPS Throughput of 3 Gbps or better		
The appliance should have minimum Firewall Threat prevention Throughput of 2.5 Gbps or better		
The appliance should have minimum IPSec-VPN Throughput of 2 Gbps or better		
The appliance should have minimum 200 Number of Ipsec VPN Peers supported (Site to Site)		
The appliance should have minimum 450 Number of Ipsec VPN Peers supported (Client to Site)		
The appliance should have minimum 200 Number of SSL VPN Peers supported (Client to Site)		
The appliance should have minimum 1.3 M Concurrent Session/Concurrent Connection		
The appliance should have minimum 800 Mbps TLS/SSL inspection throughput (DPI SSL)		
The appliance Should support 80+ Web categories		
The appliance Should support 3000+ application Signature		
The appliance Should support 5000+ IPS Signature		
The appliance should have minimum 450K Deep Packet Connection.	-	-
Firewall Security Features	J	

Page 29 of 44

The Firewall should scan for threats in both inbound and outbound and intra-	
zone traffic for malware in files of unlimited length and size across all ports	
and TCP streams by GAV & Cloud AV.	
The proposed firewall should support Bi-directional raw TCP inspection that	
scans raw TCP streams on any port.	
The Firewall must support Proxy-less and non-buffering inspection	
technology for DPI scanning without introducing file and stream size	
limitations.	
The Firewall should support deep packet SSL to decrypt HTTPS traffic for scanning(IPS, Gateway Antivirus, Content Filtering, Application control)	
transparently for future requirement and then re-encrypt and send to	
destination if no threat found.	
The firewall must support cloud & appliance based Sandbox technology and	
OEM must have own cloud & appliance based Sandboxing & Advanced	1
Threat Protection solutions.	
The cloud or appliance based sandbox should have technology that detects	
and blocks malware that does not exhibit any malicious behavior and hides	1 1
its weaponry via encryption. Should detect and block mass-market, zero-day	
threats and unknown malware.	
The Firewall should have the capability to block/prevent from Side Channel	
attacks, memory based attack as well as zeroday malware and Never-before-	
seen malware attack.	
Should support both for analysis of a broad range of file types, either	
individually or as a group, including executable programs (PE), DLL, PDFs,	
MS Office documents, archives, JAR, and APK plus multiple operating	
systems including Windows, Android, Mac OS X and multi-browser	
environments.	
Should have ability to prevent potentially malicious files from entering the	
network and those files sent to the sandbox for analysis to be held at the	
gateway until a verdict is determined. The Firewall sholud have Pictorial view of a particular access rule, NAT and	
Routing rule which helps in finding real-time statistics. Displays the rules	
which are actively used or not being used & enabled or disabled.	
The proposed system should have the future option to integrate with cloud-	
based management & reporting system to manage Firewall. Both solutions	
should be from the same OEM.	
The proposed system should be SD WAN Enable without adding any additional hardware components & Necessary licenses, if required, need to be	
	1
provisioned from day 1. The integarted cloud based sandboxing must have capability to scans 10Mb	
of files size at a time.	
The proposed Firewall should have ability to prevent potentially malicious	
files from entering the network and files sent to the cloud based or on-	1
premises sandbox for analysis to be held at the gateway until a verdict is	1
determined.	
The Firewall should detect and prevent hidden attacks that leverage	1
cryptography, blocks encrypted malware downloads, ceases the spread of	1
infections, and thwarts command and control (C&C) communications and	1
data exfiltration	
License , Certification And Warranty	
Warranty - 3 years comprehensive onsite warranty including 24x7 telephone,	
email and web-based technical support.	
OEM should have TAC and R&D center in INDIA.	
Manufacturer's warranty should be mentioned minimum 03 (three) years	
warranty including all services like GAV, IPS, Antispyware or antimalware,	
CFS, Application control, BoT protection, Advance Threat Protection, Patch	
& Firmware upgrade and Hardware.	
Bidder must carry out on site installation, testing and commissioning.	
	1 1

Page 30 of 44



OEM should have scored minimum 97% in Exploit Block rate in the last NSS Lab report for NGFW (2019)	
The Firewall OEM must be ICSA Lab certified for Network Firewall, Anti- virus and ATD and should have detection rate of 99% or higher.	
The proposed appliance should come from firewall appliance family which has ICSA labs certification/NSS/NDP/ Indian Standard, IC3S/Common Criteria.	

(2) Distribution Switch - L3 Switch with 24 SFP ports 2 10GBASET ports 4 10G SFP ports L3 Stackable Managed Switch	Compliance (Yes/No)	Remarks
Switch Specification		
Switch with at least 24 X SFP Ports, 2 x 10G Base-T and 4 X SFP+ Ports.		
Switch should have console port for accessing the CLI of the switch.		
Switch should have RJ-45 port for out-of band-management port	l i	
Switch should have USB port for connecting a USB storage device.		
Switching capacity should be 168 Gbps or higher or non-blocking architecture.		
Switch shall have 64 Bytes packet forwarding rate should be 125 Mpps or higher		
Switch MAC table should be at least 16K or higher.		
Switch should be standard 19 inch 1U rack mountable.		
Switch should Support Internal/External Redundant Power Supply.		
Switch should support Physical Stacking up to 9 units per stack. Stacking bandwidth should be up to 80G and up to 32 devices per virtual stack.		
Operating temperature should be 0 to 50 °C.		
Switch should be EMI Certificates FCC, CE and Safety Certifications cUL/UL, CB.		
Switch Software Specification		
Should have 802.1D STP, 802.1w RSTP and 802.1s MSTP Spanning Tree Protocol and ERPS as per standard ITU-T G.8032 to provide protection for Ethernet traffic in ring topology.		
Should support BPDU Filter, BPDU restriction, Root restriction		
Should support Loopback detection (LBD) to detect the loop created by a specific port.		
Should support IGMP Snooping v1/V2/V3 & IGMP groups 1K or more IGMP groups and require support for IGMP Snooping Fast Leave.		
Should support MLD Snooping v1/v2 & MLD group 1K or more and require support for MLD Snooping Querier.		
Should support 16 L3 IP interfaces and IPv4/IPv6 Loopback interface.	l l	
Should support IPv6 Neighbor Discovery (ND).		
Should support VRRPv3, Equal-Cost Multi-Path (ECMP) and UDP		
helper. Should support Static route for both IPv4 and IPv6, OSPFv1, v2 & v3, RIP V1/V2/ng.		
Should have Policy-based Route (PBR).		
Switch should support IEEE 802.1Q VLAN with different type of VLAN like Port based, Voice VLAN, Private, Double (Q-In-Q), Multicast VLAN (ISM		

Page 31 of 44

Riston Pia



VLAN for IPv4/IPv6), 802.1v Protocol VLAN ,VLAN Trunking, Super VLAN		
should have per-port broadcast, multicast, and unicast storm control to		
from degrading overall systems performance.		
Should support port security to secures the access port based on MAC address.		
Require prevention of DoS attacks, which include Land, Blat, TCP Null Scan, TCP Xmas Scan, TCP SYNFIN, Ping of Death Attack and TCP Tiny Fragment attack.		
Should support DHCP snooping and DHCP server screening, DHCP		
Should support 802.1X port based and 802.1X host based access control,Identity-		
(VLAN, ACL or QoS) Assignment Should support RADIUS and TACACS+ authentication.		
Should support Authentication database failover.		
Switch should support QoS (quality of service) IEEE 802.1P for traffic prioritization. It should support 8 queues per port.		
Different type of QoS priority like Strict Priority Queue and Weighted Round Robin, Strict + WRR,		
Congestion control using Weighted Random Early Detection (WRED) or WTD		
Should support Remark 802.1p priority, Remark ToS/DSCP and Rate limiting in		
Policy man		
Support at least 2K ingress & 512 egress access control entries. ACL on MAC, IPv4 and		
based On MAC, 1FV4 and IPv6, TCP/UDP port number, User-defined packet content, CPU Interface Filtering. Should support time based ACL.		
Able to manage trough Web-GUI, Fully functional CLI interface and Telnet.		
Should have multiple Image and configuration support to reduced down time for the switches.		
Should support sFlow for monitoring traffic in data networks, SNMP v1, v2c, v3 and SNMP Traps and		
RMON. Support for DHCP Client support for IPv4/IPv6, DHCP server, DHCP Relay and DNS		
client.		
Should have SNTP/NTP protocol for time synchronization. Should support CDP/UDLD, Link Layer Discovery Protocol (LLDP) and LLDP-MED.		
Access Switch- 24 PoE+ port L2 with minimum 2 SFP	Compliance	Remarks
Managed) Switch with at least 24 X 10/100/1000 Mbps PoE Ports and 4 x	(Yes/No)	
10G SFP+ Ports.		
Switching capacity should be 128Gbps or higher or non-		
blocking architecture.	-	
Switch packet forwarding rate should be 95.24 Mpps or higher or non-blocking architecture.		
Switch Should Support IEEE 802.3af & at compliance (for PoE ports) and 370W Power Budget.		

Page 32 of 44



Switch MAC table should be	
Switch MAC table should be at least 16K or higher.	1 1 1
Switch should be standard 19 inch 1U rack mountable.	
Support for the Energy Efficient Ethernet (IEEE 802.3az) standard.	
Power input should be 100 to 240 VAC, 50/60 Hz, internal	
T oupply.	
Operating temperature should be -5 degree celsius to +50 degree celsius.	
Certification: CE, FCC, BSMI, RoHS and cUL.	
Switch Software Specification	
Should support Head of Line blocking prevention for lower	
latency and better performance.	
Support Jumbo Frame up to 12K Bytes or higher	
Should support IGMP Snooning Able to greate 250	
I Give groups and require support for IGMP Spooning Fact	
Leave, 10 Mr Shooping Olierier	
Should support MLD Snooping. Able to create 250 or many	
WILD groups, Per VLAN MLD Snooning and require support	
To WLD Shooping Fast Leave.	
Should have 802.1D STP, 802.1w RSTP and 802.1s MSTP	
Spanning Tree Protocol.	
Should support Spanning tree Root restriction	
Should support Loopback detection (LBD) to detect the loop	
created by a specific port.	
Should support Multicast Filtering to filters or forward all unregistered groups.	
Switch should support IEEE 802.1Q VLAN tagging for Ethernet	
trames.	
Different type of VLAN like Port based, Auto Surveillance,	
Auto Voice, Asymmetric Vlan etc. should be available for	
configuration.	
Switch should support QoS (quality of service) IEEE 802.1P for	
traffic prioritization. It should support 8 queues per port.	
Different type of QoS priority like Strict Priority Queue and	
Weighted Round Robin.	
Port based ingress / egress rate limit function should be	
available with limit in increments as low as 16 Kbps	
Switch should support Neighbor Discovery (ND) protocol for	
IPv6.	
Switch should support to create at least 4 IP interface	
Should support default routing and static routing with minimum	
100 IPv4 static route entries and minimum 50 IPv6 static route entries.	
Support at least 700 rules shared by IPv4, MAC, and IPv6 &	
Each rule can only be associated with a single port.	
Should support port security to secures the access port based on	
MAC address.	

Page 33 of 44

should have broadcast, multicast, and unicast storm control to prevents faulty end stations from degrading overall systems		
performance.	FA	
Support Traffic Segmentation to restricted traffic flow from a single or group of ports, to a another group of ports.		
Should have SSH and SSL for IPv4 and IPv6.		
Require prevention of DoS attacks, which include Land, Blat, TCP Null Scan, TCP Xmas Scan and TCP SYNFIN.		
Should support 802.1X port based authentication.		
Should support ARP spoofing prevention.		
Should support DHCP snooping and DHCP server screening.		
Switch should able to create a binding table for IP + MAC +		
Port to prevents a malicious user from spoofing or to restrict the		
Should support 802.1X RADIUS and local server database authentication.		
Should have option to check the status of copper cables using the cable-diagnostics time domain reflectometer (TDR).		
Able to manage trough Web-GUI, CLI, Telnet & SNMP		
Should support SNMP v1, v2c, v3 and SNMP Traps and Remote Monitoring (RMON).		
Should have dual Image support to reduced down time for the switches.		
Switch should support dynamic host configuration protocol (DHCP) auto configuration of multiple switches through a boot server eases switch deployment.		
Should have SNTP/NTP protocol for time synchronization.		
Switch should be IPv6 Ready Compliance.		
Should support Link Layer Discovery Protocol (LLDP) and LLDP-MED.		
Note		
Switch should be supplied with the all necessary components		
like Power cord, Rack-mount bracket, Installation Guide, etc.		
and necessary software image file to fulfil all above mention		
feature set from day 1.		
Access Switch-8 port L2 PoE with minimum 2 SFP	Compliance	Remarks
(Managed)	(Yes/No)	
Switch Should Support 8 10/100/1000BASE-T PoE and 2 SFP ports		
Switch Should Support Min. 20 Gbps Switching Capacity and Maximum 64 Byte Packet Forwarding Rate is 14.88 MPPS		
The Switch shall have the intelligence to detect the loop occurring from the unmanaged network segment.		
Switch Should Support IEEE 802.3af & at compliance (for PoE ports) and 130W Power Budget.		
Switch Should Support IGMP Snooping v1, v2 and MLD snooping v1/v2		

Page 34 of 44



Switch shall support IEEE 802.1AB Link Layer Discovery Protocol (LLDP) & LLDP-MED. Switch Should Support IEEE 802.3az Energy Efficient Ethernet (EEE) Power saving Technology, Power Saving by Link Status, Time-based PoE, System hibernation, Port shut off, Cable length detection Etc. Switch Should Support 4K VLAN ID's, Min 256 static VLAN Switch Should Support Port Mirroring One to one/Many to One Switch Should Support Quality of Service (QoS), 802.1p, Strict, Weighted Round Robin (WRR), Bandwidth Control. Switch Should Support Min 4 IP interfaces, Static routing for inter-VLAN Communication Switch Should Support Security Features like Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port-based Access Control , Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support Management thru Web-based and compact CLI. Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) Remarks (Yes/No) Remarks (Yes/No) Remarks (Hall) have a robust design for durability It shall have bardened enclosures for indoor deployment and shall have a robust design for durability It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45. AP shall support	Switch shall support IEEE 802 1AB Link Layer Discovery	1	10
Protocol (LLDP) & LLDP-MED. Switch Should Support IEEE 802.3az Energy Efficient Ethernet (EEE) Power saving Technology, Power Saving by Link Status, Time-based PoE, System hibernation, Port shut off, Cable length detection Etc. Switch Should Support 4K VLAN ID's, Min 256 static VLAN Switch Should Support Port Mirroring One to one/Many to One Switch Should Support Quality of Service (QoS), 802.1p, Strict, Weighted Round Robin (WRR), Bandwidth Control. Switch Should Support Min 4 IP interfaces, Static routing for inter-VLAN Communication Switch Should Support Access Control List (ACL), Port Base, MAC Base, IP Based, L2 & L3 ACL (IPv4 and IPv6) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port-based Access Control , Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Server, Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Server, Sonoping, Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support Management thru Web-based and compact CLI. Switch Should Support Management thru Web-based and compact CLI. Switch Should Support for Urability It shall have a robust design for durability It shall have simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbp	Switch shall support inche out in the arms and		
Ethernet (EEE) Power saving Technology, Power Saving by Link Status, Time-based PoE, System hibernation, Port shut off, Cable length detection Etc. Switch Should Support 4K VLAN ID's, Min 256 static VLAN Switch Should Support Port Mirroring One to one/Many to One Switch Should Support Quality of Service (QoS), 802.1p, Strict, Weighted Round Robin (WRR), Bandwidth Control. Switch Should Support Min 4 IP interfaces, Static routing for inter-VLAN Communication Switch Should Support Access Control List (ACL), Port Base, MAC Base, IP Based, L2 & L3 ACL (IPv4 and IPv6) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port-based Access Control , Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) Remarks (Yes/No) Remarks (124 GHz) operation It shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have a robust design for durability It shall have a robust design for durability It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Protocol (LLDP) & LLDP-MED.		
Ethernet (EEE) Power saving Technology, Power Saving by Link Status, Time-based PoE, System hibernation, Port shut off, Cable length detection Etc. Switch Should Support 4K VLAN ID's, Min 256 static VLAN Switch Should Support Port Mirroring One to one/Many to One Switch Should Support Quality of Service (QoS), 802.1p, Strict, Weighted Round Robin (WRR), Bandwidth Control. Switch Should Support Min 4 IP interfaces, Static routing for inter-VLAN Communication Switch Should Support Access Control List (ACL), Port Base, MAC Base, IP Based, L2 & L3 ACL (IPv4 and IPv6) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port-based Access Control , Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) Remarks (Yes/No) Remarks (124 GHz) operation It shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have a robust design for durability It shall have a robust design for durability It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Switch Should Support IEEE 802.3az Energy Efficient		
by Link Status, Time-based PoE, System nibernation, Pot shut off, Cable length detection Etc. Switch Should Support 4K VLAN ID's, Min 256 static VLAN Switch Should Support Port Mirroring One to one/Many to One Switch should support Quality of Service (QoS), 802.1p, Strict, Weighted Round Robin (WRR), Bandwidth Control. Switch Should Support Min 4 IP interfaces, Static routing for inter-VLAN Communication Switch Should Support Access Control List (ACL), Port Base, MAC Base, IP Based, L2 & L3 ACL (IPv4 and IPv6) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port-based Access Control , Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) AP shall have a robust design for durability It shall have simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Ethornot (EEE) Power saving Technology, Power Saving		-
shut off, Cable length detection Etc. Switch Should Support 4K VLAN ID's, Min 256 static VLAN Switch Should Support Port Mirroring One to one/Many to One Switch Should support Quality of Service (QoS), 802.1p, Strict, Weighted Round Robin (WRR), Bandwidth Control. Switch Should Support Min 4 IP interfaces, Static routing for inter-VLAN Communication Switch should support Access Control List (ACL), Port Base, MAC Base, IP Based, L2 & L3 ACL (IPv4 and IPv6) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port- based Access Control, Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have bardened enclosures for indoor deployment and shall have a robust design for durability It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	by Link Status, Time-based PoE, System hibernation, Port		4
Switch Should Support Port Mirroring One to one/Many to One Switch Should Support Port Mirroring One to one/Many to One Switch Should Support Quality of Service (QoS), 802.1p, Strict, Weighted Round Robin (WRR), Bandwidth Control. Switch Should Support Min 4 IP interfaces, Static routing for inter-VLAN Communication Switch Should Support Access Control List (ACL), Port Base, MAC Base, IP Based, L2 & L3 ACL (IPv4 and IPv6) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port-based Access Control , Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE, VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	shut off Cable length detection Etc.		
Switch Should Support Port Mirroring One to one/Many to One Switch should support Quality of Service (QoS), 802.1p, Strict, Weighted Round Robin (WRR), Bandwidth Control. Switch Should Support Min 4 IP interfaces, Static routing for inter-VLAN Communication Switch should Support Access Control List (ACL), Port Base, MAC Base, IP Based, L2 & L3 ACL (IPv4 and IPv6) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port-based Access Control , Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: Cc, VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Switch Should Support 4K VLAN ID's, Min 256 static	3	
Switch Should Support Port Mirroring One to one/Many to One Switch should support Quality of Service (QoS), 802.1p, Strict, Weighted Round Robin (WRR), Bandwidth Control. Switch Should Support Min 4 IP interfaces, Static routing for inter-VLAN Communication Switch should support Access Control List (ACL), Port Base, MAC Base, IP Based, L2 & L3 ACL (IPv4 and IPv6) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port-based Access Control, Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	13/1/481		
One Switch should support Quality of Service (QoS), 802.1p, Strict, Weighted Round Robin (WRR), Bandwidth Control. Switch Should Support Min 4 IP interfaces, Static routing for inter-VLAN Communication Switch should support Access Control List (ACL), Port Base, MAC Base, IP Based, L2 & L3 ACL (IPv4 and IPv6) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port- based Access Control, Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE, VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Switch Should Support Port Mirroring One to one/Many to		
Switch should support Quality of Service (QoS), 802-1p, Strict, Weighted Round Robin (WRR), Bandwidth Control. Switch Should Support Min 4 IP interfaces, Static routing for inter-VLAN Communication Switch should support Access Control List (ACL), Port Base, MAC Base, IP Based, L2 & L3 ACL (IPv4 and IPv6) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port-based Access Control, Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	One		
Strict, Weighted Round Robin (Wrk'), Ballowin Control. Switch Should Support Min 4 IP interfaces, Static routing for inter-VLAN Communication Switch should support Access Control List (ACL), Port Base, MAC Base, IP Based, L2 & L3 ACL (IPv4 and IPv6) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port-based Access Control , Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Quite should support Quality of Service (QoS), 802.1p,		
Switch Should Support Min 4 IP interfaces, Static routing for inter-VLAN Communication Switch should support Access Control List (ACL), Port Base, MAC Base, IP Based, L2 & L3 ACL (IPv4 and IPv6) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port-based Access Control , Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Strict Weighted Round Robin (WRR), Bandwidth Control.		
for inter-VLAN Communication Switch should support Access Control List (ACL), Port Base, MAC Base, IP Based, L2 & L3 ACL (IPv4 and IPv6) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port- based Access Control, Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE, VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Switch Should Support Min 4 IP interfaces, Static routing		
Switch should support Access Control List (ACL), Port Base, MAC Base, IP Based, L2 & L3 ACL (IPv4 and IPv6) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port-based Access Control, Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Switch Stiduld Support Will 1 in Interest of		
Base, MAC Base, IP Based, L2 & L3 ACL (IFV4 and IFV4) Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port- based Access Control, Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	for inter-VEAN Communication		
Switch Should Support Security Features like Broadcast/Multicast/Unicast Storm Control, Traffic segmentation, TLS, DoS attack prevention, 802.1X Port- based Access Control, Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE, VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Switch should support Access Control List (ACL), 1 St. (A		
Broadcast/Multicast/Unicast Storm Control, Trainic segmentation, TLS, DoS attack prevention, 802.1X Portbased Access Control, Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Base, MAC Base, IP Based, L2 & L3 AOL (II V Turk III)		
segmentation, TLS, DoS attack prevention, 802.1X Pott-based Access Control , Port Security, ARP Spoofing Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Switch Should Support Security Features like		
based Access Control , Port Security, ARP Spooling Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Broadcast/Multicast/Unicast Storm Control, Hame		1
Prevention, DHCP Server Screening, IP-MAC-Port Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	segmentation, TLS, DoS attack prevention, 802.177 of		
Binding, ARP Inspection, DHCP Snooping. Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	based Access Control , Port Security, ARP Spooting		
Switch Should Support 802.1X Authentication local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE, VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Prevention, DHCP Server Screening, IP-WAC-POR		
local/RADIUS database (IPv4 & IPv6), port-based access control, EAP, OTP, TLS, TTLS, PEAP and Support MD5 authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Binding, ARP Inspection, DHCP Shooping.		
control, EAP, OTP, TLS, TTLS, PEAP and Support MDS authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Switch Should Support 802.1X Authentication		
authentication Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	local/RADIUS database (IPV4 & IPV6), port-based access		
Switch Should Support features Cable diagnostics, IPv4 & IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	control, EAP, OTP, TLS, TTLS, PEAP and Support MIDS		
IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	authentication Cable diagnostics IPv4 &		
HOL Blocking Prevention Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Switch Should Support features Cable diagnostics, IFV4 &		
Switch Should Support Management thru Web-based and compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	IPv6 Inspection, SSH v2 feature, 802.3x Flow Control and		
compact CLI. Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	HOL Blocking Prevention		
Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP v6, IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Switch Should Support Management thru Web-based and		
IPv4/v6 Dual Stack, Dual image, Dual configuration Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II Compliance (Yes/No) AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	compact CLI.		
Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Switch Should Support SNMP v1/v2c/v3, SNTP, ICMP vo,		
Certifications • EMI: CE , VCCI, FCC, BSMI and Safety: CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	IPv4/v6 Dual Stack, Dual image, Dual configuration		
CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Certifications • EMI: CE , VCCI, FCC, BSMI and Safety:		
AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	Octanodations —		
AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	CR III BSML CCC		Damanla
and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	CR III BSML CCC		Remarks
and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II		Remarks
2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment		Remarks
2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability		Remarks
1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.	CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability		Remarks
Minimum 1 number of 1 Gbps Ethernet port RJ-45.	CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation		Remarks
Minimum 1 number of 1 Gbps Ethernet port RJ-45.	CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and		Remarks
	CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds		Remarks
7 ii Oliali Gapport Malia ago, milio	CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds		Remarks
AP shall support Outfitted with the latest 802.11ac Wave 2	CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45. AP shall support Multi user MIMO		Remarks
technology	CB, UL, BSMI, CCC Indoor AP (With Mounting Kit & Controller) - II AP shall have hardened enclosures for indoor deployment and shall have a robust design for durability It shall have dual radios for concurrent dual band (5 GHz / 2.4 GHz) operation It shall have Simultaneous 574 Mbps on 2.4GHz and 1201 Mbps on 5GHz totals 1775 Mbps Wi-Fi speeds Minimum 1 number of 1 Gbps Ethernet port RJ-45.		Remarks

Page 35 of 44

The AP shall comply with IEEE 802.11ac at a minimum	1	1
and be backwards compatible to IEEE 802.11a/b/g/n		
standards.		
AP shall operate at least in full 2x2:2 MIMO or more mode	1	
without any loss of features or capabilities		
AP shall Support PoE 802.3af and passive PoE for	1	
convenient and affordable installation		
AP must support 20 MHz, 40 MHz and 80 MHz channels.	İ	
Each AP must support minimum 50+ concurrent clients in		
total (including both 2.4GHz and 5GHz radios).		
The AP shall provide a minimum of 20 dBm EIRP for both		
2.4 GHz and and 23 dBm for 5 GHz frequencies. Field		
deployment shall be with EIRP as per regulatory		
guidelines.		
AP shall support QoS and WMM latest technology		
AP shall support Multiple operating modes including		
managed AP and standalone AP mode		
AP shall support Band Steering, Beamforming, Airtime		
Fairness and Load Balance features		
AP shall support rogue access point detection		
AP shall have dual-Band Omni-directional Antenna, either		
internal or external. Field deployment shall be with EIRP		
as per the WPC guideline.		
AP should be compatible for Simple mounting on any wall		
or ceiling surface		
AP should support management VLAN		
AP should support Captive portal and Rate limit feature		
AP shall support Reboot Schedule, Wireless Schedule		
and Wireless Statistics based on SSID/AP/Client		
Intelligent RF control plane for self-healing, and self-		
optimization		
AP Shall support Wireless Mac Address Filtering, Wireless		
Isolation Between Clients and SSID to VLAN Mapping		
AP shall support 802.1X authentication and external		
radius server		
AP shall be able to assign end User the IP address as		
received from backend core DHCP Server.		
AP shall support Hardware controller or software controller		
Shall support Operating Temperature of 32°F~144°F		
Device OEM must be ISO 9001 and 14001 Certified		
Shall support Operating Temperature of -30°C~70°C		
Device OEM must be ISO 9001 and 14001 Certified		
Rugged and waterproof Outdoor IP 65 AP (With Mounting	Compliance	
Kit)	(Yes/No)	Remarks
AP shall have Durable, weatherproof enclosure for	(2.00.10)	
outdoor Wi-Fi deployment and shall have a robust design		
for durability		
It shall have dual radios for concurrent dual band (5 GHz /		
2.4 GHz) operation		

Page 36 of 44



5GHz Wi-Fi speeds Minimum one number of 1 Gbps Ethernet port RJ-45.	
AP shall support Multi user MIMO	
AP shall support Outfitted with the latest 802.11ac	
technology	
The AP shall comply with IEEE 802.11ac at a minimum	
and be backwards compatible to IEEE 802.11a/b/g/n	
standards.	
AP shall operate at least in full 2X2:2 MIMO or more mode	
without any loss of features or capabilities	
AP shall Support PoE 802.3af and passive PoE for	
convenient and affordable installation	
AP must support 20 MHz, 40 MHz Channel Width	
The AP shall provide a minimum of 20 dBm EIRP for both	
2.4 GHz and and 27 dBm for 5 GHz frequencies. Field	
deployment shall be with EIRP as per regulatory	
guidelines.	
AP shall support WDS or MESH networking*	
AP shall support QoS and WMM latest technology	
AP shall support Multiple operating modes including	
managed AP and standalone AP mode	
AP shall support Band Steering, Beamforming, Airtime	
Fairness and Load Balance features	
AP shall support rogue access point detection	
AP shall have dual-Band Omni-directional Antenna, either	
internal or external.	
AP should be compatible for Simple mounting on any wall	
or ceiling surface	
AP should support management VLAN and SSID VLAN	-
AP should support Captive portal and Rate limit feature	
AP shall support Reboot Schedule, Wireless Schedule	
and Wireless Statistics based on SSID/AP/Client	
Intelligent RF control plane for self-healing, and self-	
optimization	
AP Shall support Wireless Mac Address Filtering, Wireless Isolation Between Clients and SSID to VLAN Mapping	
AP shall support 802.1X authentication and external	
radius server	
AP shall be able to assign end User the IP address as	
received from backend core DHCP Server.	
AP shall support Hardware controller or software controller	
and must be SDN Ready	
AP Shall support ZTP (Zero Touch Provisioning) for	
seamless Installations	
Shall support L3 management, SNMP, Email notification	
Shall support Operating Temperature of -30°C~70°C	
Device OEM must be ISO 9001 and 14001 Certified	

Page 37 of 44



Cat 6 Cable (Per Box 305 meter)		Compliance (Yes/No)
eatures	Category 6 Unshielded Twisted Pair 4 pair cable shall be compliant with ANSI/TIA/EIA-568-C.2 channel performance.	
	Category 6 UTP cables shall extend between the work area location and its associated telecommunications closet and consist of 4 pair, 23 AWG, UTP.	
	The 4 pair Unshielded Twisted Pair cable shall be ETL Verified	
Mechanical Characte	ristics	
Construction: 4 twisted	d pairs separated by internal X shaped, 4 . Half shall not be accepted.	
Conductor dia	23 AWG	
Insulation	POLYETHYLENE	
Pairing	TWISTED INTO TWO CORE	
No.of Pair	4 PAIR TWISTED TOGETHER	
Color of sheath	PVC GREY- Single sheath	
RIP CORD	YES	
Sequential meter marking	YES	
Temperature Rating	(- 20 to +60 C)	
Filler Required	YES	
Packing	305 Mtrs.	
Low Frequency Elec	trical Parameter	
CONDUCTOR RESISTANCE (DC)	93.8 OHMS/1000 MTR @20 Degree C. MAX.	
RESISTANCE UNBALANCE	5%MAX	
MUTUAL CAPACITANCE	5.6 nF/100 mtrs Max.	
CAPACITANCE UNBALANCE PAIR/GROUND	330PF/100M MAX	
Propagation Delay Skew	536 nS/100M	
Nominal Velocity of Propagation	69%	
Charcteristics IMPEDANCE	100±15%OHMS	
Worst Case cable skew	45ns/100m o EIA/TIA 568-C.2 and IEC/ISO 11801	
Generally commining to	CLIATIA 500-0.2 and ILONOO 11001	

Page 38 of 44

Ritos) & Bir



IO box for CAT-term	ination	(Yes/No)
Single Port	Write on labels in transparent plastic window – supplied with plate	
	Face Plate with shutter	
	Should be able to support variety of jacks – UTP, STP etc.	
	Category 6, TIA568 C.2	
	All information outlets for 22-26 AWG copper cable shall:	
	Use insulation displacement connectors (IDC)	
	Allow for a minimum of 200 reterminations without signal degradation below standards compliance limits.	
Insertion force:	20N max	
	Jack Specification:	
Plastic Housing:	Polycarbonate, UL94V-2 rated or equivalent	
Operating Life:	Minimum 750 insertion cycles	
Contact Material:	Phosphor Bronze with nickel plated	
	Contact Plating: 50 µinches gold on plug contact area	
IDC:	Housing PC , UL 94 V-2, 568A/B configuration	
	Operating Life: Minimum 200 Reterminations	
IDC Contact Plating:	Phosphor bronze with tin plated	
Operation Temp	: -10 C to 60 C	
6 Core Fibre with LIU and termination with all accessories		Compliance (Yes/No)
FIBER CABLING COMPONENTS	Optical Fiber Cable	
Single mode (SM) Fiber, Standard properties		
GENERAL:	The 6 core armored fiber cable type is a Matched Cladding Single Mode	
	Fiber dual coated with acryl ate coating.	
	The fiber is optimized for operation at 1310 nm and at 1550 nm.	
	Should fulfill the requirements of:	
	The state of the s	

Page 39 of 44



	IEC 60793-1/60794-1-2	I
	· ISO 11801	
	· ITU-T REC G.652.D	
GEOMETRICAL PROPERTIES:	Nominal mode field diameter: 9.2 μm	
	Mode field diameter tolerance: ±4%	
	Cladding diameter: 125 µm	
	Cladding diameter tolerance : ±1 µm	
	Mode field concentricity error : < 1 μm	
	Cladding non-circularity: < 2 %	
MATERIALS	Germanium doped core with no phosphorus i.e. reduced tendency for hydrogen degradation.: CORE	
	UV-curable dual layer acryl ate coating, which ensures excellent micro bending and abrasion resistance.: COATING	
	Stripping force after conditioning at 23± 5 °C at 40 - 60 % RH for 24 h.	
	Min.: 1.0 N	
	Max.: 3.5 N	
	Stripping force after ageing in water at 70 ± 5 °C for 168 h.	
	Min.: 1.0 N	
	Max.: 3.5 N	
OPTICAL PROPERTIES	Attenuation (of cable with fibers):	
	At 1310 nm: <= 0.36 dB/km	
	In the range 1285-1330 nm: <= 0.40dB/km	
	At 1550 nm: <= 0.22 dB/km	
	Cut-off wavelength Ic:	
	High limit: 1330 nm	
	Low limit: 1180 nm	
	Cut-off wavelength lcc	
	High limit: 1260 nm	
	Loss increase at 1550 nm for 100 turns of fiber loosely wound with a 37.5 mm radius:	
	Max. : 0.1 dB	
	Dispersion:	
	Zero dispersion wavelength: 1310 nm	
	Tolerance of zero dispersion	
	Wavelength: -10/+12 nm	

Page 40 of 44




	Zero-dispersion slope:	
	Max.: 0.092 ps/(nm² · km)	
	Chromatic dispersion coefficient:	
	In 1285 nm - 1330 nm interval:	
	Max : 3 5ps/km • nm	
	In 1270 nm - 1340 nm interval	
	Max.: 6 ps/km • nm	
	At 1550 nm	
	May 19 ng/km • nm	
	Polarisation Mode Dispersion (PMD):	
	Max.: <=0.2 ps/km	
	In homogeneity of OTDR trace for any two 1000 meter fiber lengths	
	Max.: 0.1 dB/km	
	Proof test level : 1%	
	Proof test level . The	
LIU- RACK MOUN	IT – 12 port LIU Loaded Single mode	Compliance (Yes/No)
	Min. Required Specification	
Characteristic	12 port Loaded LIU accommodate LC	
	Single mode adapters.	
	Cold steel base material with powder coating. Aluminum top and front cover for light mounting	
	can manage both splices and terminations	
	should have fiber magic sticker provision inside for 900um tight buffered fiber storing	
	Accessory kit consists of cable ties, mounting ear screw earthing.	
	Front-Mounted Cable Saddles for jumper management	
	Removable Top & Front cover for better access to interior of LIU	
	Removable Top & Front cover for better	

Page 41 of 44



	Adapters should have compact design & high precision.	
•	which perform well under various circumstances & maintain good plug retention strength.	
Optical Fiber Pigtail	– LC Type 3 Meter	Compliance (Yes/No)
Characteristic Features	Min. Required Specification Provide a field installable Single mode LC pigtails to terminate fiber optic cables from cable-to-cable, cable-to-equipment and equipment-to-equipment.	
	Utilize a UPC polishing on the tip to provide high yield during installation.	
	Meet TIA/EIA 568.C.3 standards for repeatability.	
Insertion Loss (Max)	<0.3 db Max.	
Mating Cycle	200 times	
Return Loss	>/= 50 db for UPC	
Connector ferrule	Ceramic	
Operating Temp.	(- 20 deg. C to + 60 deg. C)	
buffer diameter	900um Tight buffer	
Types	LC Type Simplex	
	nent Cords (minimum 1 meter) - LC-LC	Compliance (Yes/No)
Characteristic	Min. Required Specification	1 2 2 2 2 2
Features	Optical fiber patch leads shall comprise of Simgle mode 9/125µm fiber with LC-LC fiber connectors terminated at each end. The optical fiber patch leads shall comply with the following specifications:	
Optical Fiber -	Single mode	
Connector:	Zirconia ceramic ferrule	
	Pre-radiuses and pre-polished ferrule	
	Duplex Type	
Color-coded	yellow	-
Insertion Loss	<0.3 db	
Cable	9/125, SM	
Return Loss	>/= 50dB for UPC	
Durability	200 mating cycle	

Page 42 of 44



Working Temp	(- 20 deg. C to + 60 deg. C)	Compliance
Length	1 Meter	(Yes/No)
(17) CONDUIT		
(17) 001.2	L Destangular	Compliance
	PVC and Rectangular	(Yes/No)
(18) 24 port LAN p	patch panel	11.00
(18) 24 port 2		
- toriotic	Min. Required Specification Patch Panel made of powder coated steel, and configurations.	
Characteristic	- I D-not made of Po-	
Features	in 24 port corrigation cano re-	
	in 24 port configurations. Allow for a minimum of 200 re- terminations without signal degradation terminations without signal degradation.	1
	terminations without signal designations limit.	
	helow standards com-	
	Have port identification numbers on the	
	Have port identification name	
	front of the parion	
	Should have sell aution window type)	
	holders (transparent plants with the	
	and white designation	
	panel and as AWG stranded and	
	IDC: Suitable for 22-20 AVV solid wire compatible with both 110 & solid wire down tools	
	" - wire compatible with a	
	Krone punch down to the	
	Improved cable management with optional	
	Improved cable management har	
	cable management but	
	The Cat-6 transmission periormality compliance with the ANSI/TIA/EIA 568C.2 compliance with the ANSI/TIA/EIA 568C.2	
	standard and ISO 11801 Class D/E/EA	
	standard and 130 Tree:	
	Plastic Housing: PBT+Glass Fiber,	
Mechanical	- " o 4) / O roted	
Characteristics	UL94V-0 rated Operating Life: Minimum 750 insertion	
Jack Connector	Operating Life: William 700 in	
Jack Comme	cycles Material: Phosher bronze with nickel	
	plated Contact Plating: 50μ" Gold plated on plug	
	Contact Plating: 50p Gold plates 50p	
	contact area	
127 CT - 27 SMAT	Contact Force: 20N max Plastic Housing: Polycarbonate, UL94V-2	
IDC Connector	Plastic Housing, Polycarbonato,	
	rated or equivalent IDC Contact Plating: Phosphor bronze	
	IDC Contact Plating. Priosphor Stories	
	with tin plated Wire Accommodation: 22-26 AWG solid	
	Wire Accommodation. 22-20 / W 5 53.14	d
	Vallege Beting: 125V AC RMS	
	Voltage Rating: 125V AC RMS	
	Contact resistance: 20Milliohms	
	Insulation resistance: 100 MegaOhms @	
	500V DC	

Page 43 of 44

Rites Pint.



UPS (2KVA)		Compliance (Yes/No)
PHASE:	SINGLE PHASE WITH GROUND	
ONLINE UPS CAPACITY:	2000VA/1600W	
NO. OF BATTERIES REQUIRED:	6	
TYPE OF BATTERY REQUIRED:	VRLA SMF	
EFFICIENCY:	87-90%	
WAVEFORM:	PURE SINE WAVE	
WARRANTY:	24 MONTHS	

Page 44 of 44



